

PRODUCT SPECIFICATION

PRODUCT NUMBER: 1631A4T

DESCRIPTION: 16 1061



SEQUEL™
WIRE & CABLE

PO Box 34 · Argos, IN 46501
151 Dewey Street · Argos, IN 46501
574-626-1515 · Fax 574-253-4036

DIAMETER: 0.078

TOLERANCE +/-: 0.003

GAUGE: 16 AWG

CONDUCTORS: 1

STRANDING: 26/30 TC LHL

INSULATION: PVC


VOLTAGE: 300V DC

TEMPERATURE: 80/105 C

STYLE: 1061/10002

PRINT LEGEND: E511593 16 AWG (1.31mm²) UR AWM
1061 80C or 10002 105C 300V VW-1 --
301259 CSA AWM I A/B 105C 300V FT1

NOTES: 1. Min Temp Rating: -40C



NOM WALL: 0.009

MINIMUM WALL: 0.007

Tolerances unless otherwise noted: FRACTIONS +/- 1/32, DECIMALS +/- 0.03 (2PL) +/-0.005 (3PL)

Revision Date: 02/21/2025 Revision: 3

Confidential: This drawing and its information are the exclusive and confidential property of Sequel Wire and Cable, LLC and are not to be disclosed, duplicated, distributed, or otherwise used without the written consent of Sequel Wire and Cable, LLC. All rights reserved.