

PRODUCT SPECIFICATION

PRODUCT NUMBER: 0435A3B

DESCRIPTION: 4 19/ BC 1283



SEQUEL™
WIRE & CABLE

PO Box 34 · Argos, IN 46501
151 Dewey Street · Argos, IN 46501
574-626-1515 · Fax 574-253-4036

DIAMETER: 0.360

TOLERANCE +/-: 0.005

GAUGE: 4 AWG

CONDUCTORS: 1

STRANDING: 19/0469 BC

INSULATION: PVC


VOLTAGE: 600V DC/1000V DC

TEMPERATURE: 105C

STYLE: MTW/AWM 1283

PRINT LEGEND: E517536 4 AWG (21.2 mm²) (UL) BC-5W2
or MTW or THHW or AWM 1011 80C or
1337 90C or 1015/1232/1283/1346 105C
600V or 1032 90C or 10269 105C 1000V
Moisture Resistant VW-1—301259 CSA TEW
or AWM I A/B 105C 600V FT1—SGT2 J1127

NOTES: 1. MIN TEMP -10C UL



NOM WALL: 0.060

MINIMUM WALL: 0.054

Tolerances unless otherwise noted: FRACTIONS +/- 1/32, DECIMALS +/- 0.03 (2PL) +/-0.005 (3PL)

Revision Date: 02/11/2026 Revision: 2

Confidential: This drawing and its information are the exclusive and confidential property of Sequel Wire and Cable, LLC and are not to be disclosed, duplicated, distributed, or otherwise used without the written consent of Sequel Wire and Cable, LLC. All rights reserved.