

PRODUCT SPECIFICATION

PRODUCT NUMBER: 2243A4T

DESCRIPTION: 22 AWM 3173



SEQUEL™

WIRE & CABLE

PO Box 34 · Argos, IN 46501

151 Dewey Street · Argos, IN 46501

574-626-1515 · Fax 574-253-4036

DIAMETER: 0.091

TOLERANCE +/-: 0.003

GAUGE: 22

CONDUCTORS: 1

STRANDING: 7/0096 TC

INSULATION: XLPE


VOLTAGE: 600V DC/1000V DC

TEMPERATURE: 125C

STYLE: AWM/3173/3237

PRINT LEGEND: E511593 22 AWG (.324mm²) UR AWM
3173 125C 600V or 3237 1000V -- 301259
CSA CL1251 125C 600V or AWM I A/B 125C
600V FT2

NOTES: 1. Insulating material tested to rate -40C



NOM WALL: 0.030

MINIMUM WALL: 0.027

Tolerances unless otherwise noted: FRACTIONS +/- 1/32, DECIMALS +/- 0.03 (2PL) +/-0.005 (3PL)

Revision Date: 09/25/2024 Revision: 2

Confidential: This drawing and its information are the exclusive and confidential property of Sequel Wire and Cable, LLC and are not to be disclosed, duplicated, distributed, or otherwise used without the written consent of Sequel Wire and Cable, LLC. All rights reserved.